Articles

Cat. No

Description


DAIHAN-brand<sup>®</sup> Premium Hotplate Stirrer, "MSH-A", Ceramic-Coated Plate, up to 380°C, 1,500 rpm, with Certi. & Traceability Built-in Linearity PWM Controller, Superior Temperature Uniformity, Precise Control of Temp. & RPM, 180×180mm or 260×260mm 아날로그 가열 자력 교반기, 우수한 온도균일성, 세라믹 코팅 플레이트



180×180mm Plate-type Hotplate Stirrer "MSH-20A"



260×260mm Plate-type Hotplate Stirrer "MSH-30A"



with Certificate & Traceability :

Controlled by Serial Number, Certificate, Delivery-information, and Traceable Data Base System

- Superior Temperature Uniformity : Less than 10% on the Plate at Ambient Temperature
- Superior Linearity for Temperature Control & Stirring Speed
- Ceramic Coated Plate-Chemical / Acid Resistance
- CE Certified
  PL(Product Liability) Insurance
- \* Excellent for Sample Drying and most General Lab Heating Applications
- \* Superior Temperature Uniformity : Less than 10% on the Plate at Ambient Temperature
- \* Superior Linearity for Temperature Control & Stirring Speed by Specially Designed Control Circuitry.(PWM Control)
- \* Smart Design of Body made by Aluminum Die-Casting (MSH-20A)
- \* Ceramic Coated Plate Chemical/Acid Resistance
- \* Maximum Temperature of 380°C

## Specification

Model		180×180mm Plate-type "MSH- 20A"	260×260mm Plate-type "MSH- 30A"	
Material	Body	Powder Coated Aluminum	Powder Coated steel	
Wateria	Plate	Ceramic Coated Aluminum (Chemical / Acid Resistance, Easy to Clear		
Stirring Capa. & Motor Rating		Max. 20 Lit., 9 / 4 W		
Speed Range		Max. 1,500 rpm		
Temp. Range		Max. 380°C		
Temp. Uniformity		Specially Designed Heating Module : Temp. Difference 10% less		
Heating Power/Consumption		600W	1.2 kW	
Controller		Superior Linearity PWM Controller		
Stirring Bar		3cm bar-included, Usable : up to 5cm bar		
Permissible Temp. & RH %		Ambient +5 ~ 50°C, 85% RH		
Dimension & Weight		206 imes 307 imesh99mm, 2.8kg	$286 \times 387 \times h99$ mm, $3.3$ kg	
Packing Size &	Gross Weight	400×280×h200mm, 5 kg	430×320×h200mm, 5 kg	
Power Supply & Cord/Plug*		1 Phase, AC 120 V, 60 Hz or AC 230 V, 50 / 60 Hz		

\* Other Specifications are available upon Customer's Request.

## Ordering Information

With 180×18	Omm Plate-type Hotplate Stirrer, "MSH-20A"	Ea.	Price, ₩
DH.WMH03120 DH.WMH02120	$180 \times 180 \text{mm}$ Plate-type, <b>230V,</b> with stir bar , <b>120V,</b> with stir bar		196,780 196,780
With $260 \times 26$	SOmm Plate-type Hotplate Stirrer, "MSH-30A"	Ea.	Price, ₩
DH.WMH03121	260×260mm Plate-type, <b>230V</b> , with stir bar		380,970
DH.WMH02121	, <b>120V,</b> with stir bar		380,970
Optional Stand Rod & Holder/Clamp			
Optional Stand	Kod & Holder/Clamp	Ea.	Price, ₩
Optional Stand DH.WHP503011	Rod & Holder/Clamp           (1) Stand Rod, "RD100", Stainless steel, Non-screw           φ12.7 × L390mm, for "HP-30A/30D", "MSH-30A/30D"	Ea.	<b>Price, ₩</b> 9,230
	(1) Stand Rod, " <b>RD100</b> ", Stainless steel, Non-screw	Ea.	,

## **Specialized Features**

